

RUST CONVERTER

Transform, Seal, & Prevent

DESCRIPTION

Rust Converter is a surface conditioner and primer that changes rust into a dark protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. This black polymer coating stands up to exposure to weather, rain, sun, and salt spray without peeling or cracking. Rust Converter is an excellent primer for use under all oil-based paints.

CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions and emergency procedures.

KEEP OUT OF REACH OF CHILDREN.

DIRECTIONS

- Shake or stir well before using
- Remove large rust and scale particles with a brush and clean the surface of grease and dirt
- Apply by brushing or rolling
- The coating will dry to a smooth, darkened finish in 20 minutes and will be fully cured after 24 hours. The cured Rust Converter coating should be sealed over with a high-quality oil-based paint (do not use water-based latex paints)
- No other primer is required
- Application equipment should be cleaned immediately with soap and water

HMIS SYMBOL





FIRST-AID

Eyes: Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation—get medical attention.

Skin: Flush with water and then wash with soap and water, launder contaminated clothing before reuse—get medical attention if irritation persists.

Inhalation: Remove to fresh air and assist breathing as necessary—get medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth with water. Get medical attention.