

## Z-PATCH

### 100% Epoxy Concrete Repair

#### DESCRIPTION

**Z-Patch** is a heavy-duty, high compression strength floor patch for repairing and resurfacing damaged plant floors. It renews and repairs spalled and damaged floors, fills and eliminates damaged expansion joints, and anchors machinery.

#### FEATURES

- 100% epoxy resin base with a catalyst hardener and special blended aggregate
- 18,000 psi compression strength
- Will not break down at temperatures below 350°F
- Withstands heavy, abusive traffic
- Absorbs vibration and shock without cracking
- Excellent for expansion and contraction applications
- Highly resistant to acids, alkalies, solvents, heat, and cold
- Extra-long wearing – permanent and resilient
- Self-leveling – minimal trowel work
- Bonds to concrete, steel and wood
- Kit covers 15-18 sq. ft. at ¼" thick

#### HOW TO USE

1. Ready floor by removing all loose material. Sweep away dirt. Degrease areas which have a thick build-up of grease.
2. Remove the cradle which contains Part B (pint) and 10 lbs. special aggregate.
3. Thoroughly mix Part A (which contains 12 lbs. special aggregate) until uniform.
4. Pour entire contents of Part (B) into Part (A), which is in the bottom of the pail. Mix Parts A & B for 2-3 minutes.
5. Add special aggregate from cradle to mixed Parts (A & B) to desired consistency, thick for troweling, thin for pouring.
6. Fill holes, cracks, crevices to level of existing floor. Feather edges with a trowel. Wet trowel with epoxy thinner and finish off to a smooth surface.

**NOTE:** You have 25-30 minutes to apply product to floor. Z-Patch dries in 12-18 hours for light traffic and 48-72 hours for heavy traffic. Each kit covers 15-18 sq. ft. at 1/4" thickness

#### SPECIFICATIONS

	<b>Part A</b>	<b>Part B</b>	<b>Part C</b>
<b>Physical Form</b>	Viscous Liquid	Liquid Hardener	Granules
<b>Color</b>	Clear to Light Amber	Clear	Gray
<b>Odor</b>	Acrylate	Amine	N/A
<b>Specific Gravity</b>	1.13	1.0	70 lb/ft
<b>Flash Point (TCC)</b>	200+°F	200+°F	None