# TRI-CHEM

#### **Safety Data Sheet**

#### **Section 1: Identification**

**Product identifier** 

Product Name • Heatcrete
Product Code • 110100

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Tri-Chem Corporation

431 Stephenson Hwy. Troy, MI 48083 United States www.tri-chem.com

Telephone (General) • 800-456-6255

**Emergency telephone number** 

Manufacturer • 1-800-535-5053

#### Section 2: Hazard Identification

**United States (US)** 

According to OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

 Serious Eye Damage 1 - H318 Carcinogenicity 1A - H350

Specific Target Organ Toxicity Repeated Exposure 2 - H373

Label elements

OSHA HCS 2012

## **DANGER**



Hazard statements • Causes serious eye damage - H318

May cause cancer. - H350

May cause damage to organs through prolonged or repeated exposure. - H373

**Precautionary statements** 

Prevention • Obtain special instructions before use. - P201

Do not handle until all safety precautions have been read and understood. - P202

Do not breathe dust. - P260

Wear protective gloves, clothing, and eye/face protection, . - P280

Response • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. - P305+P351+P338 Immediately call a POISON CENTER or doctor/physician. - P310 IF exposed or concerned: Get medical advice/attention. - P308+P313

Storage/Disposal • Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations. - P501

#### Other hazards

**OSHA HCS 2012** 

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

#### Canada

**According to WHMIS** 

#### Classification of the substance or mixture

**WHMIS** 

 Other Toxic Effects - D2A Other Toxic Effects - D2B Corrosive - E

# Label elements WHMIS





 Other Toxic Effects - D2A Other Toxic Effects - D2B Corrosive - E

#### Other hazards

**WHMIS** 

 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## Section 3 - Composition/Information on Ingredients

#### **Substances**

Material does not meet the criteria of a substance.

#### **Mixtures**

Composition							
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments		
Mullite	<b>CAS</b> :1302- 93-8	40.27% TO 46.6%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA		
Cement, alumina, chemicals	<b>CAS</b> :65997- 16-2	4.8% TO 16%	NDA	OSHA HCS 2012: Not Classified	NDA		
Silica, amorphous	<b>CAS</b> :7631-86-9	4.3% TO 14.2%	NDA	OSHA HCS 2012: Not Classified	NDA		
Bauxite	<b>CAS</b> :1318- 16-7	< 14%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs);	NDA		

Cristobalite	<b>CAS</b> :14464-46-1	6.498% TO 12.165%	NDA	<b>OSHA HCS 2012</b> : Carc. 1A	NDA
Calcium Aluminate	Proprietary	2% TO 8%	NDA	OSHA HCS 2012: Eye Dam. 1; Skin Irrit. 2; STOT SE 3: Resp. Irrit.;	NDA
Aluminum oxide	<b>CAS</b> :1344-28-1	0% TO 8%	Inhalation-Rat LC50 • 0.2 mg/L 5 Hour(s) 28 Week (s)	OSHA HCS 2012: Not Classified	NDA
Aluminum(III) silicate (2:1)	<b>CAS</b> :1302-76-7	2.55% TO 6.65%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA
Quartz	<b>CAS</b> :14808-60-7	0.15% TO 0.78%	NDA	<b>OSHA HCS 2012:</b> Carc. 1A; STOT RE 1 (Lungs);	NDA
Titanium dioxide	<b>CAS</b> :13463-67-7	0.03% TO 0.59%	NDA	OSHA HCS 2012: Carc. 2;	NDA
Amorphous/fused silica	<b>CAS</b> :60676-86-0	0% TO 0.48%	NDA	OSHA HCS 2012: Not Classified	NDA
Iron oxide	<b>CAS</b> :1309- 37-1	0% TO 0.32%	NDA	OSHA HCS 2012: Not Classified	NDA
Magnesium oxide	<b>CAS</b> :1309-48-4	0% TO 0.048%	NDA	OSHA HCS 2012: Exposure limits	NDA
Sodium hydroxide	<b>CAS</b> :1310-73-2	0% TO 0.04%	NDA	OSHA HCS 2012: Exposure limits	NDA
Calcium oxide	<b>CAS</b> :1305-78-8	0% TO 0.016%	NDA	OSHA HCS 2012: Exposure limits	NDA

#### Section 4: First-Aid Measures

#### **Description of first aid measures**

Inhalation

IIIIIaiatioii

Skin

Eye

Ingestion

 Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately.

• In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

• In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

 Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

## Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

## Indication of any immediate medical attention and special treatment needed

**Notes to Physician** 

All treatments should be based on observed signs and symptoms of distress in the
patient. Consideration should be given to the possibility that overexposure to materials
other than this product may have occurred.

## Section 5: Fire-Fighting Measures

## Extinguishing media

**Suitable Extinguishing Media** • Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

Unsuitable Extinguishing Media

None known.

## Special hazards arising from the substance or mixture

Unusual Fire and Explosion • None known.

#### **Hazards**

## **Hazardous Combustion**

Products

None known.

#### **Advice for firefighters**

Wear positive pressure self-contained breathing apparatus (SCBA).
 Structural firefighters' protective clothing will only provide limited protection.
 Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

#### Section 6 - Accidental Release Measures

## Personal precautions, protective equipment and emergency procedures

**Personal Precautions** 

 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.

**Emergency Procedures** 

 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

#### **Environmental precautions**

No specific actions or treatments recommended related to exposure to this material.

## Methods and material for containment and cleaning up

Containment/Clean-up Measures

Avoid generating dust.

FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).

FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

## **Section 7 - Handling and Storage**

#### Precautions for safe handling

Handling

• Do not breathe dust. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash thoroughly after handling. Do not use in areas without adequate ventilation.

## Conditions for safe storage, including any incompatibilities

**Storage** 

 Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

## Section 8 - Exposure Controls/Personal Protection

## Control parameters

Exposure Limits/Guidelines							
	Result ACGIH Canada Ontario Canada Quebec Mexico NIOSH						
Sodium hydroxide (1310-73-2)	Ceilings	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	
	STELs	Not established	Not established	Not established	10 mg/m3 STEL [LMPE-CT] (as Fe)	Not established	

Iron oxide (1309-37-1)	TWAs	5 mg/m3 TWA (respirable fraction)	5 mg/m3 TWA (respirable)	5 mg/m3 TWAEV (dust and fume, as Fe); 10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, regulated under Rouge, total dust)	5 mg/m3 TWA LMPE- PPT	5 mg/m3 TWA (dust and fume, as Fe)
Calcium oxide (1305-78-8)	TWAs	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWAEV	2 mg/m3 TWA LMPE- PPT	2 mg/m3 TWA
Magnesium oxide (1309-48-4)	TWAs	10 mg/m3 TWA (inhalable fraction)	10 mg/m3 TWA (inhalable)	10 mg/m3 TWAEV (fume, as Mg)	10 mg/m3 TWA LMPE-PPT (fume, as Mg)	Not established
Aluminum oxide (1344-28-1)	TWAs	1 mg/m3 TWA (respirable fraction) as Aluminum insoluble compounds	1 mg/m3 TWA (respirable) as Aluminum insoluble compounds	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust, as AI)	10 mg/m3 TWA LMPE-PPT	Not established
Amorphous/fused silica (60676-86-0)	TWAs	Not established	0.1 mg/m3 TWA (respirable)	0.1 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)	0.1 mg/m3 TWA LMPE-PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	10 mg/m3 TWA LMPE-PPT (as Ti)	Not established
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Silica, amorphous (7631-86-9)	TWAs	Not established	Not established	Not established	Not established	6 mg/m3 TWA
Cement, alumina, chemicals as Particulates not otherwise classified (PNOC)	TWAs	10 mg/m3 TWA (inhalable particles, recommended); 3 mg/m3 TWA (respirable particles, recommended) as Particulates not otherwise classified (PNOC)	10 mg/m3 TWA (inhalable); 3 mg/m3 TWA (respirable)  as Particulates not otherwise classified (PNOC)	10 mg/m3 TWAEV (including dust, inert or nuisance particulates; containing no Asbestos and <1% Crystalline silica, total dust) as Particulates not otherwise classified (PNOC)	Not established	Not established

Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)		05 mg/m3 TWAEV espirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
		Ехр	osure Limits/Gu	idel	ines (Con't.)		
			Result		OSHA		
Sodium hydroxide (1310-73-2)			TWAs		2 mg/m3 TWA		
Iron oxide (1309-37-1)			TWAs		10 mg/m3 TWA (fu 15 mg/m3 TWA (to dust, listed under Rouge); 5 mg/m3 T (respirable fraction listed under Rouge	tal WA n,	
Calcium oxide (1305-78-8)			TWAs		5 mg/m3 TWA		
Magnesium oxide (1309-48-4)			TWAs		15 mg/m3 TWA (fu total particulate)	me,	
Aluminum oxide (1344-28-1)			TWAs		15 mg/m3 TWA (to dust); 5 mg/m3 TW (respirable fraction	/A	
Titanium dioxide (13463-67-7)			TWAs		15 mg/m3 TWA (to dust)	tal	
Cement, alumina, chemicals			TWAs		15 mg/m3 TWA (to dust); 5 mg/m3 TW (respirable fraction as Particulates no otherwise classifie (PNOC)	/A n) t	

# **Exposure Limits Supplemental OSHA**

- •Cristobalite (14464-46-1): **Mineral Dusts:** ((1/2)(30)/(%SiO2 + 2) mg/m3 TWA, total dust; (1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)
- Quartz (14808-60-7): Mineral Dusts: ((30)/(%SiO2 + 2) mg/m3 TWA, total dust; (250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2
- + 2) mg/m3 TWA, respirable fraction)
- Amorphous/fused silica (60676-86-0): Mineral Dusts: ((80)/(% SiO2) mg/m3 TWA; 20 mppcf TWA)
- •Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)

## **Exposure controls**

## Engineering Measures/Controls

• Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace.

#### **Personal Protective Equipment**

#### Respiratory

 For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

Wear appropriate gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

#### General Industrial Hygiene Considerations

Avoid breathing dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash hands before eating, drinking, or smoking. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

#### **Environmental Exposure** Controls

Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

#### Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

OSHA = Occupational Safety and Health Administration

Time-Weighted Averages are based on 8h/day, 40h/week TWA

## Section 9 - Physical and Chemical Properties

#### Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties			
Boiling Point	No data available	Melting Point	No data available
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	2.2 to 2.9 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
VOC (Vol.)	0 %		
Flammability			
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental	•	•	•
Octanol/Water Partition coefficient	No data available		

## Section 10: Stability and Reactivity

## Reactivity

No dangerous reaction known under conditions of normal use.

## Chemical stability

Preparation Date: 22/May/2013 Format: GHS Language: English (US) Revision Date: 22/December/2014 WHMIS, OSHA HCS 2012 Page 7 of 13

Stable under normal temperatures and pressures.

## Possibility of hazardous reactions

• Hazardous polymerization not indicated.

#### Conditions to avoid

None known.

#### **Incompatible materials**

None known.

## **Hazardous decomposition products**

None known.

## **Section 11 - Toxicological Information**

## Information on toxicological effects

	Components					
Titanium dioxide (0.03% TO 0.59%)	13463- 67-7	Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors				
Cristobalite (6.498% TO 12.165%)	14464- 46-1	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Cough; Lungs, Thorax, or Respiration:Dyspnea;  Multi-dose Toxicity: Inhalation-Mouse TCLo • 43 mg/m³ 5 Hour(s) 9 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Pleural effusion; Lungs, Thorax, or Respiration:Other changes				
Silica, amorphous (4.3% TO 14.2%)	7631-86- 9	Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation				

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • No data available
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2
STOT-SE	OSHA HCS 2012 • No data available
Toxicity for Reproduction	OSHA HCS 2012 • No data available
Respiratory sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • Serious Eye Damage 1

Route(s) of entry/exposure Medical Conditions Aggravated by Exposure Potential Health Effects Inhalation

- Inhalation, Skin, Eye, Ingestion
- Any pre-existing conditions of the lungs. Disorders of the lungs.

**Acute (Immediate)** • Exposure to dust may cause irritation.

#### **Chronic (Delayed)**

 Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking.

#### Skin

Acute (Immediate)

**Chronic (Delayed)** 

Exposure to dust may cause irritation.

No data available.

## Eye

Acute (Immediate)

 Causes serious eye damage. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

No data available.

**Chronic (Delayed)** 

#### Ingestion

**Acute (Immediate)** 

 Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

**Chronic (Delayed)** 

Carcinogenic Effects

No data available.

 May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Carcinogenic Effects					
CAS IARC NTP					
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Not Listed		
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen		
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed		

#### Key to abbreviations

TC = Toxic Concentration

## Section 12 - Ecological Information

#### **Toxicity**

Material data lacking.

### Persistence and degradability

Material data lacking.

## **Bioaccumulative potential**

Material data lacking.

#### **Mobility in Soil**

Material data lacking.

#### Other adverse effects

No studies have been found.

## Section 13 - Disposal Considerations

#### Waste treatment methods

**Product waste** 

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## **Section 14 - Transport Information**

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## **Section 15 - Regulatory Information**

## Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Acute, Chronic

State Right To Know						
Component	CAS	MA	NJ	PA		
Aluminum oxide	1344-28-1	Yes	Yes	Yes		
Calcium oxide	1305-78-8	Yes	Yes	Yes		
Cristobalite	14464-46-1	Yes	Yes	Yes		
Quartz	14808-60-7	Yes	Yes	Yes		
Silica, amorphous	7631-86-9	Yes	Yes	Yes		
Sodium hydroxide	1310-73-2	Yes	Yes	Yes		
Titanium dioxide	13463-67-7	Yes	Yes	Yes		

	Inventory						
Component	CAS	Canada DSL	Canada NDSL	TSCA			
Aluminum oxide	1344-28-1	Yes	No	Yes			
Calcium oxide	1305-78-8	Yes	No	Yes			
Cristobalite	14464-46-1	Yes	No	Yes			
Quartz	14808-60-7	Yes	No	Yes			
Silica, amorphous	7631-86-9	Yes	No	Yes			
Sodium hydroxide	1310-73-2	Yes	No	Yes			
Titanium dioxide	13463-67-7	Yes	No	Yes			

#### Canada

Labor Canada - WHMIS - Classifications of Substances		
Calcium oxide	1305-78-8	Е
Sodium hydroxide	1310-73-2	E (including 0.04% in aqueous solution, 0.08%, 0.4% in aqueous solution, 2%, 2.5%, 4% in aqueous solution, 5%, 10%, 16%, 20%, 40%, 50% in aqueous solution, 8.7N)

Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
<ul> <li>Cristobalite</li> <li>Silica, amorphous</li> </ul>	14464-46-1 7631-86-9	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)  Uncontrolled product according to WHMIS classification criteria
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Canada - WHMIS - Ingredient Disclosure List		
Calcium oxide	1305-78-8	1 %
Sodium hydroxide	1310-73-2	1 %
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1 %
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
• Quartz	14808-60-7	1 %

## **United States**

1305-78-8	Not Listed
1310-73-2	1000 lb final RQ; 454 kg final RQ
13463-67-7	Not Listed
1344-28-1	Not Listed
14464-46-1	Not Listed
7631-86-9	Not Listed
14808-60-7	Not Listed
1305-78-8	Not Listed
1310-73-2	Not Listed
13463-67-7	Not Listed
	13463-67-7 1344-28-1 14464-46-1 7631-86-9 14808-60-7 1305-78-8 1310-73-2

Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

#### **United States - California**

U.S California - Proposition 65 - Carcinogens List		
Calcium oxide	1305-78-8	Not Listed
Sodium hydroxide	1310-73-2	Not Listed
Titanium dioxide	13463-67-7	carcinogen, initial date 9/2/11 (airborne, unbound particles respirable size)
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/8 (airborne particles of respirable size)

#### **United States - Pennsylvania**

J.S Pennsylvania - RTK (Right to Know) - Environm	nental Hazard List	
Calcium oxide	1305-78-8	Not Listed
Sodium hydroxide	1310-73-2	
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

#### Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

#### Section 16 - Other Information

Last Revision Date
Preparation Date

Disclaimer/Statement of Liability

- 22/December/2014
- 22/May/2013
- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Tri-Chem Corporation MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## Key to abbreviations

NDA = No data available